

2

1

PCB Load & Torque Inc. claims proprietary rights in the information disclosed hereon. Neither it nor any reproduction thereof will be disclosed to others without the written consent of PCB Load and Torque Inc.

REVISIONS


REV	DESCRIPTION	ECO
A	ADDED NOTE - 12.10.24, PTE	55424

46142



4 CONDUCTOR BLACK SHIELDED
CABLE 10.0 FT [3.0 M] LONG
TERMINATING IN PIGTAILS
(WESTERN REGIONAL WIRING)

STRAIN RELIEF



3.50 [88.9]

2.50 [63.5]

2X M16x2 - 6H
THRU ONE WALL

Ø.65 [16.5]

.75 [19.1]

1.61 [41.0]

1.50 [38.1]

2.00 [50.8]

1.25 [31.8]

2.55 [64.8]



OPTIONAL CABLE TERMINATIONS AVAILABLE

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE:

DIMENSIONS IN INCHES

DIMENSIONS IN MILLIMETERS
[IN BRACKETS]

DECIMALS XX ±.01
XXX ±.005

DECIMALS X ±.03
XX ±.013

ANGLES ± .5 DEGREES

ANGLES ± .5 DEGREES

FILLETS AND RADII
.015 MAX

FILLETS AND RADII
0.38 MAX

DRAWN

CHECKED

ENGINEER

SMB

06.20.11

JM

06.20.11

JAM

6/29/11

TITLE

OUTLINE DRAWING
MODEL M1631-06C
S-CELL

PCB LOAD & TORQUE
A PCB GROUP COMPANY

24350 Indoplex Circle, Farmington Hills, MI 48335
(716) 684-0001 E-MAIL: ltinfo@pcbloadtorque.com

DWG. NO.

46142

SCALE: FULL

SHEET 1 OF 1

2

1