

IEPE signal conditioner

Model 4416C



Key features

- Low noise operation
- Portable compact size
- Selectable gain of 1, 10 or 100
- Status indicator LED
- 2nd order Sallen Key low pass filter

Description

Model 4416C IEPE signal conditioner is a small, battery-operated, low noise signal conditioner for use with IEPE transducers. It supplies power to the transducer from a constant current source, and provides a selectable gain of 1, 10 or 100. The conditioner is powered by a rechargeable Li-Ion battery. An LED status indicator informs the user of a short, open, or normal operating conditions. Additionally the unit features a second order Sallen Key low pass filter.

Specifications	
Input characteristics	
Type	Single-ended, constant current two-wire system
Input impedance	>20 k Ω
Excitation current	4.7 mA ($\pm 5\%$)
Maximum input voltage	7.07 Vpk (5 vrms)
Compliance voltage	24V ($\pm 1\%$)
Transducer status LED	Green = OK, Red = fault (open or short circuit)
Output characteristics	
Type	Single-ended, one side connected to circuit ground
Output impedance	<10 Ω , in series with at least 47 μ F
Linear output voltage (Min)	10Vpk (7.07 V rms)
Linear output current (Max)	2mA
Transfer characteristics	
Frequency range	Gain = 1: -5% 0.3 Hz to 30 kHz; -3dB 0.1 Hz to 100 kHz
Filter out	Gain = 10: -5% 0.5 Hz to 30 kHz; -3dB 0.15 Hz to 100 kHz Gain = 100: -5% 0.5 Hz to 20 kHz; -3dB 0.15 Hz to 50 kHz
Filter In	LP filter (as supplied); 2nd order Sallen Key Gain = 1 & 10: >-5% @ 10 kHz; > -3dB @ 30 kHz Gain = 100: >5% @ 10 kHz; > -3dB @ 18 kHz
Gain	x1, x10 and x100, user selectable
Gain Accuracy	$\pm 1\%$
Harmonic distortion	<1.0%, 20Hz to 30kHz, 100mV – 10V pk.
Noise (filter out)	Gain = 1: <20 μ V rms Gain = 10: <200 μ V rms Gain = 100: <2mV rms
Power	
Batteries	Internal Lithium Ion
Typical battery life	8 hours minimum continuous use
External power supply	12 VDC (1.5A minimum)
Recharge cycle time	Unit off, approximately 3 hours
Charger LED indication	Red = battery low, Yellow = battery charging
Physical	
Charger connector	2.5mm male jack plug
Dimensions	3.3" W x 1.4" H x 7.1" D (82 mm x 35 mm x 179 mm)
Weight	13 oz (370 gm) $\pm 5\%$
Connections	BNC for both Input and Output
Case	Aluminum, black painted
Environmental	
Temperature	
Operating (battery being discharged)	-10°C to +60°C (+14°F to +140°F)
Operating (battery being charged)	-10°C to +45°C (+14°F to +113°F)
Storage (Li-Ion battery)	-5°C to +35°C (23°F to +95°F) De-rated for long-term storage for lithium batteries -40°F to +122°F (-40°C to +50°C)
Humidity	95% R.H.
Compliance	ROHS to 2011/65/EU CE to EN61326-1:2013; CFR47 Pt 15 B Class A.

IEPE signal conditioner | Model 4416C

Accessories		
Product	Description	4416
IM4416C	Instruction Manual	Download from website
EHM2107	Universal power supply 12 VDC, 2 AMP with adaptors for USA, Europe, Japan and Australia	Included
EJ21	10-32 to BNC adapter	Optional
EHM2106	Replacement Battery	As required
CS500	Calibration certificate	Included

Ordering information

1. Maintain high levels of precision and accuracy using Endevco's factory calibration services. Call Endevco's inside sales force at 866-ENDEVCO for recommended intervals, pricing and turn-around time for these services as well as for quotations on our standard products.



10869 NC Highway 903, Halifax, NC 27839 USA

endevco.com | sales@endevco.com | 866 363 3826

© 2022 PCB Piezotronics - all rights reserved. PCB Piezotronics is a wholly-owned subsidiary of Amphenol Corporation. Endevco is an assumed name of PCB Piezotronics of North Carolina, Inc., which is a wholly-owned subsidiary of PCB Piezotronics, Inc. Accumetrics, Inc. and The Modal Shop, Inc. are wholly-owned subsidiaries of PCB Piezotronics, Inc. IMI Sensors and Larson Davis are Divisions of PCB Piezotronics, Inc. Except for any third party marks for which attribution is provided herein, the company names and product names used in this document may be the registered trademarks or unregistered trademarks of PCB Piezotronics, Inc., PCB Piezotronics of North Carolina, Inc. (d/b/a Endevco), The Modal Shop, Inc. or Accumetrics, Inc. Detailed trademark ownership information is available at www.pcb.com/trademarkownership.

EDV-DS-4416C-0922