

Model Number HT378B02	ICP MICROPHONE SYSTEM	Revision: F ECN #: 47338
---------------------------------	------------------------------	-----------------------------

	<u>ENGLISH</u>	<u>SI</u>	
Performance			
Nominal Microphone Diameter	1/2"	1/2"	
Frequency Response Characteristic(at 0° incidence)	Free-Field	Free-Field	
Sensitivity	50 mV/Pa	50 mV/Pa	[4]
Sensitivity(± 1.5 dB)	-26 dB re 1 V/Pa	-26 dB re 1 V/Pa	[4]
Frequency Range(± 2 dB)	3.5 to 20,000 Hz	3.5 to 20,000 Hz	
Frequency Range(± 1 dB)	6 to 10,000 Hz	6 to 10,000 Hz	
Lower Limiting Frequency(-3 dB)	1.0 to 2.75 Hz	1.0 to 2.75 Hz	
Inherent Noise	16 dB(A) re 20 µPa	16 dB(A) re 20 µPa	[3]
Dynamic Range(3% Distortion Limit)	138.5 dB re 20 µPa	138.5 dB re 20 µPa	[3]
TEDS Compliant	Yes	Yes	[5]
Environmental			
Temperature Range(Operating)	-40 to +257 °F	-40 to +125 °C	[2]
Temperature Coefficient of Sensitivity(+14 to +158°F (-10 to +70°C))	0.005 dB/°F	0.009 dB/°C	[3][4]
Static Pressure Coefficient	-0.013 dB/kPa	-0.013 dB/kPa	[3][4]
Humidity Coefficient of Sensitivity(0 to 100%, non-condensing)	± 0.001 dB/%RH	± 0.001 dB/%RH	[4]
Influence of Axial Vibration(0.1g (1 m/s ²))	63 dB re 20 µPa	63 dB re 20 µPa	[3]
Electrical			
Polarization Voltage	0 V	0 V	[1]
Excitation Voltage	20 to 32 VDC	20 to 32 VDC	
Constant Current Excitation	2 to 10 mA	2 to 10 mA	
Output Bias Voltage	10 to 14 VDC	10 to 14 VDC	
Maximum Output Voltage	± 7 Vpk	± 7 Vpk	
Output Impedance	<55 Ohm	<55 Ohm	
Physical			
Housing Material	Stainless Alloy	Stainless Alloy	
Venting	Rear	Rear	[6]
Electrical Connector	BNC Jack	BNC Jack	
Mounting Thread(Grid)	0.5 - 60 UNS	0.5 - 60 UNS	
Size (Diameter x Height)(with grid)	.52 in x 3.88 in	13.2 mm x 98.6 mm	
Size (Diameter x Height)(without grid)	.50 in x 3.84 in	12.7 mm x 97.5 mm	
Weight	1.74 oz	49.2 gm	[3]

OPTIONAL VERSIONS

Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.

NOTES:

[1] Prepolarized
 [2] Limited to 120°C if ICP current > 4 mA
 [3] Typical.
 [4] re 250 Hz
 [5] TEDS Capable Digital Communication, compliant with IEEE 1451.4
 [6] Venting through Preamp.
 [7] See PCB Declaration of Conformance PS065 for details.

SUPPLIED ACCESSORIES:
 Model ACS-63 Calibration (with TEDS) of Precision Condenser Microphones and Preamplifiers together (mated pair). (1)

Entered: LK	Engineer: MT	Sales: MV	Approved: MT	Spec Number:
Date: 10/20/2017	Date: 10/20/2017	Date: 10/20/2017	Date: 10/20/2017	57825



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.



Phone: 716-684-0001
Fax: 716-684-0987
E-Mail: info@pcb.com