



Model LK

Triple splice assembly for 4-conductor cable to (3) 1-ft coaxial cables each to a SMA plug

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

**Toll-free: 716-684-0001
24-hour SensorLine: 716-684-0001
Fax: 716-684-0987
E-mail: info@pcb.com
Web: www.pcb.com**



Model Number LK	CABLE CONNECTOR			Revision: NR ECN #:	
Performance Connector Style Connector Style Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range Physical Electrical Connections Electrical Connections Electrical Connections ROHS Compliant Size (Length)		ENGLISH Triple Splice SMA Plug (male pin) Threaded 1/4-36 female Heat Shrink -67 to +230 °F X axis Y axis Z axis No 12 in		SI Triple Splice SMA Plug (male pin) Threaded 1/4-36 female Heat Shrink -55 to +110 °C X axis Y axis Z axis No 30.5 mm	
		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.			
		Entered: <i>Lot</i> Engineer: <i>UJN</i> Sales: <i>JDm</i> Approved: <i>ALH</i> Spec Number:			
		Date: <i>1-9-09</i> Date: <i>1/9/09</i> Date: <i>1/9/09</i> Date: <i>1/9/09</i> 41995			
		 PCB PIEZOTRONICS ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com			

All specifications are at room temperature unless otherwise specified.
In the interest of constant product improvement, we reserve the right to change specifications without notice.