



Model PA

2-socket straight high temperature (+356 F) PPS connector with stainless steel collar and FKM heat shrink strain relief **Not field installable, no individual sales**

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

**Toll-free: 716-684-0001
24-hour SensorLine: 716-684-0001
Fax: 716-684-0987
E-mail: info@pcb.com
Web: www.pcb.com**



Model Number PA	CABLE CONNECTOR				Revision: NR ECN #: 42594										
Performance Connector Style ENGLISH MIL-C-5015 Connection Type 2-socket Connection Type Jack (female socket / receptacle) Coupling Method Threaded Coupling Thread 5/8-24 female Strain Relief Molded Boot Environmental Temperature Range -67 to +356 °F Physical Size (OD x Length x Height) .75 in x 1.63 in x 1.5 in Weight 0.65 oz 		SI MIL-C-5015 2-socket Jack (female socket / receptacle) Threaded 5/8-24 female Molded Boot -55 to +180 °C 19.1 mm x 41.4 mm x 38.1 mm 18.4 gm 		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. 											
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Group, Inc.		<table border="1"> <tr> <td>Entered: AP</td> <td>Engineer: jg</td> <td>Sales: HJB</td> <td>Approved: BAM</td> <td>Spec Number:</td> </tr> <tr> <td>Date: 2/26/2014</td> <td>Date: 2/26/2014</td> <td>Date: 2/26/2014</td> <td>Date: 2/26/2014</td> <td>58212</td> </tr> </table>		Entered: AP	Engineer: jg	Sales: HJB	Approved: BAM	Spec Number:	Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	58212	 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	
Entered: AP	Engineer: jg	Sales: HJB	Approved: BAM	Spec Number:											
Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	Date: 2/26/2014	58212											
		3425 Walden Avenue, Depew, NY 14043													