



Model PB

2-socket right angle high temperature (+356 F) PPS connector with stainless steel collar and FKM heat shrink strain relief **Not field installable, no individual sales**

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

**Toll-free: 716-684-0001
24-hour SensorLine: 716-684-0001
Fax: 716-684-0987
E-mail: info@pcb.com
Web: www.pcb.com**



Model Number PB	CABLE CONNECTOR				Revision: NR ECN #: 37637
Performance Connector Style MIL-C-5015 Connector Style Right Angle Connection Type 2-socket Connection Type Jack (female socket / recepticle) Coupling Method Threaded Coupling Thread 5/8-24 female Strain Relief Molded Boot Environmental Temperature Range -67 to +356 °F Physical Size (OD x Length x Height) 0.75 in x 1.63 in x 1.50 in Weight 0.65 oz <i>All specifications are at room temperature unless otherwise specified.</i> <i>In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.		SI MIL-C-5015 Right Angle 2-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot -55 to +180 °C 19.1 mm x 41.4 mm x 38.1 mm 18.4 gm		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
Entered: DMW		Engineer: JDK		Sales: JJM	Approved: BAM
Date: 11/15/2011		Date: 11/15/2011		Date: 11/15/2011	Date: 11/15/2011
				Spec Number: 51509	
 PCB PIEZOTRONICS ELECTRONICS DIVISION 3425 Walden Avenue, Depew, NY 14043		Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: electronics@pcb.com			