



Model PV

5-Pin M12 Connector used with AzimaDLI Trio Data Collector

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

**Toll-free: 716-684-0001
24-hour SensorLine: 716-684-0001
Fax: 716-684-0987
E-mail: info@pcb.com
Web: www.pcb.com**



Model Number PV	CABLE CONNECTOR				Revision: NR ECN #: 42947
Performance	ENGLISH	SI	OPTIONAL VERSIONS		
Connector Style	Circular	Circular	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
Connector Style	Multi-conductor	Multi-conductor			
Connection Type	5-pin	5-pin			
Connection Type	Plug (male pin)	Plug (male pin)			
Coupling Method	Threaded	Threaded			
Coupling Thread	No English equivalent	M12 x 1 Male			
Strain Relief	Optional	Optional			
Environmental					
Temperature Range	-40 to +185 °F	-40 to +85 °C			
Physical					
Housing Material	PBT, Black	PBT, Black			
Size (OD x Length)	.78 in x 2.4 in	20 mm x 61 mm			
Weight	.83 oz	23.5 g			
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.					
ICP® is a registered trademark of PCB Group, Inc.					
			 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com 3425 Walden Avenue, Depew, NY 14043		