



Model QK

3-socket, Hi-Temp to 325 deg F, molded

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

Toll-free: 716-684-0001

24-hour SensorLine: 716-684-0001

Fax: 716-684-0987

E-mail: info@pcb.com

Web: www.pcb.com



Model Number QK	CABLE CONNECTOR				Revision: NR ECN #: 46529
Performance Connector Style MIL-C-5015 Connector Style Multi-conductor Connection Type 3-socket Connection Type Jack (female socket / recepticle) Coupling Method Threaded Coupling Thread 5/8-24 female Strain Relief Molded Boot Environmental Temperature Range -67 to +356 °F Physical Size (OD x Length) 0.83 in x 2.44 in Weight 0.65 oz		SI MIL-C-5015 Multi-conductor 3-socket Jack (female socket / recepticle) Threaded 5/8-24 female Molded Boot -55 to +180 °C 21.08 mm x 61.98 mm 18.4 gm		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	
<i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i> ICP® is a registered trademark of PCB Group, Inc.		Entered: LK Date: 2/28/2017		Engineer: RB Date: 2/28/2017	Sales: MC Date: 2/28/2017
		Approved: BAM Date: 2/28/2017		Spec Number: 66264	
		 3425 Walden Avenue, Depew, NY 14043		Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com	