



Model SP

5-socket M12 connector with single axis RTD accelerometer pinout Molded connector, not for individual sale

Installation and Operating Manual

**For assistance with the operation of this product,
contact the PCB Piezotronics, Inc.**

**Toll-free: 716-684-0001
24-hour SensorLine: 716-684-0001
Fax: 716-684-0987
E-mail: info@pcb.com
Web: www.pcb.com**



Model Number SP	CABLE CONNECTOR			Revision: NR ECN #: 53483
Performance Connector Style Connector Style Connection Type Connection Type Coupling Method Coupling Thread Strain Relief Environmental Temperature Range Enclosure Rating Physical Electrical Connections(Contact 1) Electrical Connections(Contact 2) Electrical Connections(Contact 3) Electrical Connections(Contact 3) Electrical Connections(Contact 4) Electrical Connections(Contact 4) Electrical Connections(Contact 5) Electrical Connections(No Connection) Electrical Connections(No Connection) ROHS Compliant Housing Material Size (OD x Length) Weight	ENGLISH Circular Multi-conductor 5-socket Plug with Female Contact Threaded No English equivalent Molded Boot -40 to +221 °F IP68 Red Black Blue Brown Green White No Connection Drain Shield Yes TPV (Santoprene), Black .58 in x 1.76 in 0.42 oz	SI Circular Multi-conductor 5-socket Plug with Female Contact Threaded M12 x 1 Female Molded Boot -40 to +105 °C IP68 Red Black Blue Brown Green White No Connection Drain Shield Yes TPV (Santoprene), Black 14.7 mm x 44.7 mm 11.8 g	OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.	